

PRODUCT NAME FTXA-AW / RXA-A

FTXA20A2V1BW / RXA20A2V1B

Capacità di Raffrescamento	Min.		kW	1.3
	Max.		kW	2.6
	Nom.		kW	2.0
Efficienza nominale	EER			4.70
	COP			5.00
	Classe energetica	Raffreddamento		A
		Riscaldamento		A
Capacità di riscaldamento	Nom.		kW	2.50
	Min.		kW	1.30
	Max.		kW	3.50

FTXA20A2V1BW / RXA20A3V1B

1.3
2.6
2.0
4.70
5.00
A
A
2.50
1.30
3.50

FTXA20A2V1BW / RXA20A5V1B

1.3
2.6
2.0
4.70
5.00
A
A
2.50
1.30
3.50

FTXA25A2V1BW / RXA25A3V1B

1.3
3.2
2.5
4.46
5.00
A
A
2.80
1.30
4.70

FTXA25A2V1BW / RXA25A5V1B

1.3
3.2
2.5
4.46
5.00
A
A
2.80
1.30
4.70

FTXA35A2V1BW / RXA35A3V1B

1.4
4.0
3.4
4.37
4.04
A
A
4.00
1.40
5.20

FTXA35A2V1BW / RXA35A2V1B

1.4
4.0
3.4
4.37
4.04
A
A
4.00
1.40
5.20

FTXA35A2V1BW / RXA35A5V1B

1.4
4.0
3.4
4.37
4.04
A
A
4.00
1.40
5.20

FTXA42A2V1BW / RXA42A2V1B

1.7
5.0
4.2
3.99
4.12
A
A
5.40
1.70
6.00

FTXA50A2V1BW / RXA50A2V1B

1.7
5.3
5.0
3.68
4.00
A
A
5.80
1.70
6.50

FTXA25A2V1BW / RXA25A2V1B (Archived)

1.3
3.2
2.5
4.46
5.00
A
A
2.80
1.30
4.70